



product details

L 36 W/840-1

Product description: L 36 W/840-1
 Product code: 4050300518107
 Quantity: Shipping carton box (VS) contains 25 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=DE&it_p=4050300518107

Categorizations	
SEG number	8329138

Certificates & Standards	
EEL - Energy Label	A

General Description	
Base (standard designation)	G13
Recycling	Yes
Rated lamp mercury content	3.0 mg

Technical - Electrical Data	
Nominal wattage (packaging)	36 W
Construction wattage	36 W
Rated lamp efficacy (HF data)	Under clarification by authority and standardization body

Technical - Geometries	
Tube diameter	26 mm
Diameter	26.00 mm
Length	970.00 mm
Length with base excl. base pins/connect	970 mm

Technical - Lifespan	
Lifespan	20000 h ¹⁾
Service life	18000 h ²⁾

Technical - Light Technical Data	
Luminous flux at 25 °C	3100 lm
Luminous flux	3100 lm
Light color	840
Color rendering index Ra	80...89
Light color as per EN 12464-1	LUMILUX Cool White

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300518091	Sleeves contains 1 Piece	188,000 mm x 27,000 mm x 985,000 mm	148,000 g (0,000 g)	0,802 Cubic dec.
4050300518107	Shipping carton box contains 25 Piece	145,000 mm x 369,000 mm x 799,000 mm	4.365,250 g (0,000 g)	51,417 Cubic dec.

Fluorescent lamps in LUMILUX and BASIC light colors offer up to 10 % energy savings compared with previous fluorescent lamps with a 38 mm tube diameter. They are designed to operate with conventional control gear and starters or with QUICKTRONIC electronic control gear. If used in starter circuits, these lamps can operate with standard control gear and recommended compensation capacitors.

For more information go to www.osram.com/system-guarantee, www.osram.com/QUICKTRONIC



28.07.2011

Subject to change without notice. Errors and omission excepted.

© 2011 OSRAM AG

Page 1 of 2



product details

L 36 W/840-1

- 1) With preheat ECG
- 2) With preheat ECG