

**DIN 94**

**Naarasokka  
Splint pin  
Шплинт  
Lõhissplint**

**ISO 1234**



d	1,6	2	2,5	3,2	3,5	4	4,5	5	6,3	8	10
d1(max.)	1,4	1,8	2,3	2,9	3,2	3,7	4,2	4,6	5,9	7,5	9,5
D1(min.)	1,3	1,7	2,1	2,7	3,0	3,5	4,0	4,4	5,7	7,3	9,3
a(max.)	2,5	2,5	2,5	3,2	3,5	4,0	4,0	4,0	4,0	4,0	6,3
b	3,2	4,0	5,0	6,4	7,0	8,0	8,5	10,0	12,6	16,0	20,0
c(min.)	2,4	3,2	4,0	5,1	6,1	6,5	7,6	8,0	10,3	13,1	16,6
c(max.)	2,8	3,6	4,6	5,8	6,8	7,4	8,2	11,8	11,8	15,0	19,0

d	L(mm)	A4 0474	Zn 0470	
1,6	10	▲		
	12	▲		
	14		▲	
	16	▲		
	20	▲	▲	
	25	▲		
	32	▣	▲	
	36	▲		
	40	▲		
2	10	▲	▲	
	12	▲		
	16	▲	▲	
	20	▲	▲	
	25	▲	▲	
	32	▣	▣	
	36	▲		
	40	▲	▲	
	50		▲	
2,5	16	▲	▲	
	20	▲	▲	
	25	▲	▲	
	32	▲	▲	
	36	▣		
	40	▲	▲	
	50	▲		
	3,2	16	▲	
		20	▲	▲
25		▲	▲	
28			▲	
32		▲	▲	
36		▣		
40		▲	▲	
50		▲	▲	
63		▲		

d	L(mm)	A4 0474	Zn 0470
3,5	50		▲
	60		▲
4	16	▣	
	20	▲	
	25	▲	▲
	32	▲	▲
	36	▲	
	40	▲	▲
	50	▲	▲
	63	▲	▲
	71	▣	▲
	4,5	50	
5	20	▣	
	25	▣	
	28		▲
	32	▲	▲
	36	▲	
	40	▲	▲
	50	▲	▲
	63	▲	▲
	71	▣	
	80	▣	▲
6,3	90	▣	
	100		▲
	32	▣	
	36	▣	
	40	▣	
	50	▲	▲
	63	▲	▲
	71	▲	▲
	80	▣	
	90	▣	

d	L(mm)	A4 0474	Zn 0470
8,0	20	▲	
	25	▲	
	32	▲	
	36	▲	
	40	▲	
	50	▲	▲
	63	▲	▲
	71	▲	
	80	▣	▲
10	90	▲	▲
	100		▲
	63		▲
100		▲	

© Ferrometal 08/2015